

The Chubbsafes range of protection cabinets for up to two hours' protection against fire.



Survivafire

FIRE-RESISTANT DOCUMENT PROTECTION

Key Features

- Highly reliable document protection using modern materials and technology.
- Tested to EN and UL 72 standards and certified by ECB•S and UL for protecting paper from fire for 60/120 minutes.
- Each drawer is protected from fire. Even if one of the drawers is accidentally left open, the other closed drawers are still protected by the built in fire resistance partitions.
- The drawers are extendable for full drawer access.
- These drawers are fitted with the new Chubbsafes slides allowing for a smooth and comfortable operation of the drawers.
- The generous capacity allows the customer to gain full advantage for their storage requirements.
- Key lock and KCL on the top drawer is standard.
- A shock absorbing plinth provides maximum impact absorption in the event of a floor collapse in a building fire.
- The Survivafire range is finished in a textured light grey paint to suit most office environments.
- An interlocking system is standard and provides the ability to control access to individual drawers.
- Pilfering of a locked drawer via an open drawer is protected against by means of a steel dividing plate between each drawer.
- The quality construction of the cabinet is evident when the drawers are fully loaded, through the quality of touch and usage.



Chubbsafes
Trusted the world over.

Product Specifications

Model	External (mm)			Internal (mm)			Weight (kg)	Capacity (litres)	Fire Resistance
	Height	Width	Depth	Height	Width	Depth			
2 Dr	817	551	779	267	387	609	207	129	60/120 mins*
3 Dr	1161	551	779	267	387	609	302	194	60/120 mins*
4 Dr	1504	551	779	267	387	609	395	259	60/120 mins*

*Survivafire is available in two levels of protection: 60 minutes and 120 minutes.

Testing

Survivafire is tested and certified by ECB•S in Europe and UL in USA for providing 60/120 minutes fire protection for paper. The test is carried out in two parts.

Fire test

Stage 1

The cabinet is placed inside the furnace which is heated to a temperature of over 1000 °C.



Stage 2

After 60 minutes in the furnace the burners are switched off. The inner temperature and humidity in the cabinet are continually monitored until the cabinet begins to cool. The cabinet remains in the furnace as the temperature returns to zero, then the cabinet is removed and opened. The maximum internal temperature inside the cabinet must not exceed 170 °C.



Impact test

Stage 1

The cabinet is placed in a pre-heated oven for up to 45 minutes. Then the cabinet is removed and dropped 9.15 metres onto a bed of rubble.



Stage 2

The cabinet is then placed back into the furnace for up to another 45 minutes. As it cools inside the furnace, the cabinet's temperature is monitored before being removed and opened. The maximum internal temperature must not exceed 170 °C.



Lock Options

All Survivafire filing cabinets come with a key lock and combination lock fitted to the upper-most drawer as standard. Optional locks are available if required.



Authorised dealer

Chubbsafes
Trusted the world over.

www.chubbsafes.com

'Chubb' is owned by Chubb plc and is a registered trademark used under license